COMMERCIAL TESTING LABORATORY, INC.

514 Main Street, P.O. Box 526 Colfax, Wisconsin 54730 715-962-3121 - 800-962-5227 FAX - 715-962-4030

WEB SITE: www.ctlcolfax.com



ANALYTICAL REPORT

Rose Pelke Plumbing N6298 State Hwy 25 Durand WI 54736

Report Number: 02010015 Page: 1 Sample Number: 02-C2667

Report Date: 5/ 3/02 Date Received: 5/ 2/02

Owner: Address:

Susan Yerigan W8998 Weber Rd

Arkansaw WI 54721

Collector: Date Sampled: 5/ 1/02

Mike Wittio Time Sampled: 9:30

Sample Source: test pump

Date Analyzed: 5/ 2/02 Time Analyzed: 14:00

Coliform, MFCC:

0 /100ml Interpretation: Bacteriologically SAFE

Nitrate-N:

0.6 ppm

Above 10 ppm Nitrate-N exceeds the recommended Public Drinking Water Standard.

Wisconsin Unique Well Number: OK 717 Date of Well Completion: 5/ 1/02

Lab Technician: Pam Gane

WI Approved Lab No. 19

(Means "LESS THAN" Detectable Level

Approved by:

W W	Well C	Constru	ction	Report	For		OK	71	7	Private Water Systems-DG/2 Department of Natural Resources		
		IN UNIQ	UE V	VELL NU	MBEK Tele	phone	- Van	a I do		Box 7921 Madison, WI 53707 (Please type or print		
Owner Susan Yerigan Number ()										using a black pen.)		
Mailing of broose the frogent see at one progen notice that for									Kdos	1. Well Location Please use decimals instead of fractions.		
Address W8998 Weber RD City State Zip Code									1.45	Town City Village Fire # (If avail.)		
City	MARK	ansaw	n nob	identifica	arris all	WI	5472	TUN IL	JE WE	of Waterville W8998 Grid or Street Address or Road Name and Number		
Cou	nty of Well I	Location		Co. Well Pen	nit	Well Cor	npletion Da	ate (mm-de	i-yy)			
	Pepin			No. W			>	1-0)	W8998 Weber RD Subdivision Name Lot # Block #		
	CONTRACTOR OF THE PARTY OF THE	The state of the s		Name)		License #		k well loca dot in corre		A gettenological sample of your wall water a		
	Pelke Plumbing, Heating & 535 40-acre parce									Gov't Lot # orNW 1/4 ofNE 1/4 of		
N6298 State Hwy 25									内	Section 05 , T 25 N; R 14 E X W		
	City				State Z	ip Code	w		E	3. Well Type New		
Durand triput bris sould no swianoline 54736 and selection									में वर्डन	Replacement Reconstruction		
hus.								i	i da	(see item 13 below) of previous unique well # constructed in 19		
				11			High Capac	S	a dead load	Reason for replaced or reconstructed well?		
4. Well se	erves 1	# of home	es and o	r	15311 68	9-211115913-2	Well?		No No	High Nitrates		
				ndustry, etc.)		HeWall	Property?		No No	Drilled Driven Point Jetted Other		
5. Is the w	ell located u	apslope or s	ideslope	e and not dow	nslope from	n any conta	mination so	ources, inc	luding tho	se on neighboring properties? Yes No If no, explain on back side.		
Well locat Distance i	ed in floodp	olain?	Yes [No (include propos	11	9. D		Yard Hydra	ant ad oz	17. Wastewater Sump 18. Paved Animal Bam Pen		
	1. Lan				200+19. Animal Yard or Shelter							
	40 2. Bui	ilding Over	hang				oundation I					
Berling to the Control of the Control	60+3. Sep		2000年年4月2日	THE REPORT OF THE PARTY OF THE	asili vit	13. B	uilding Dra	injarti z	er show	200+21. Barn Gutter 10 30005510 and		
-	75+4. Sev	THE RESERVE OF THE PARTY OF THE	高級。但於中央主	nit bedullo	d factor b					Other 22. Manure Pipe Gravity Pressure		
San Series		nconformin		Oil Tank	et black					Pressure Cast Iron or Plastic Other 23. Other Manure Storage		
	6. Buried Home Heating Oil Tank 7. Buried Petroleum Tank 15. Collector Sewer:units											
				Pool (circle on	e)		learwater S			25. Other NR 812 Waste Source		
6. Drillho	ole Dimensio		Upper	Enlarged	Drillhole:	infants	of mald	DNR USE	9.4 (514)	Geology From To		
Dia. (in.)	From (ft.)	To (ft.)	Metho	od of Constr	ruction		a. The i	ONLY	Тур	e, Caving/Noncaving, Color, Hardness, Etc. (ft.) (ft.)		
2 ()	1. Rotary - Mud Circulation							Topsoil surface 1				
10	surface 180 2. Rotary - Air 3. Rotary - Foam							William to the control of the set beautiful to the beautiful to the set of the second second				
	3. Rotary - Poarm 4. Reverse Rotary							Non-Caving Clay 1 114				
	170		1 4.	Reverse Rota	ry				NOI1-C	aving Clay 1 114		
6	180	360	The second second	Reverse Rota Cable-tool Bi		lia.			Limes	aving Clay		
6	180	360	☐ 5.	Cable-tool Bi	tin. c	Qin. dia	g depth	IC NW	Limes	stone 30 14 28		
6	180	360	☐ 5.	Cable-tool Bi Temp. Outer Removed?	casing 1	Qin. dia	g depth		Limes	stone 114 28		
6	180	360	☐ 5. ☐ 6.	Cable-tool Bi Temp. Outer Removed? If no, explain	casing 1	Qin. dia	depth	Control of the contro	Limes	stone 114 28 Sandstone about the second of the second seco		
6	180		5. 6.	Cable-tool Bi Temp. Outer Removed? If no, explain Other	casing 1	Qin. dia	g depth	C Solve Colored	Limes	stone 114 28 Sandstone about the second of the second seco		
7.	A	Casin Material, W	5. 6. 7. g, Liner eight, Sp	Cable-tool Bi Temp. Outer Removed? If no, explain Other , Screen pecification	it in. c Casing Yes [why not	Oin. dia No	To is		Limes White	stone 14 28 Sandstone 15 160		
7. Dia. (in.)	N Man	Casin Material, W ufacturer &	5. 6. 7. g, Liner eight, Sp	Cable-tool Bi Temp. Outer Removed? If no, explain Other , Screen pecification d of Assembly	it in. c Casing Yes [] Yes [] why not	Oin. dia No	Va Vino	Control of the Contro	Limes White	stone 14 28 Stone 28 28 42 Stone 42 160 Stone 5 28 28 42 Stone 6 160 270 Sandstone 2 Ventanta 28 28 28 270 Sandstone 2 Ventanta 28 28 28 270 Sandstone 3 Ventanta 28 28 28 28 28 28 28 28 28 28 28 28 28		
7.	Man New BI	Casin Material, W ufacturer &	5. 6.	Cable-tool Bi Temp. Outer Removed? If no, explain Other T, Screen pecification d of Assemble STM A-5	it in. c Casing Yes [] Yes [] why not	Oin. dia No	To is		Limes White	stone 14 28 Sandstone Third is invested to see 42 Stone 42 160 Stone 42 160 Sandstone Third is invested to see 42 160 Stone 42 160 270		
7. Dia. (in.)	New BI	Casin Material, W ufacturer & K ST 1	5. 6. 7. g, Linereight, Sp. Method	Cable-tool Bi Temp. Outer Removed? If no, explain Other T, Screen pecification d of Assembly STM A-5	Casing 1 Yes Can why not 2 3 GR E	Oin. dia No From (ft.) surface	To (ft.)	C SIGN FOR SIGN C SIGN SIGN SIGN SIGN SIGN SIGN SIGN SIGN SIGN SIGN SIGN SIGN SIGN	Limes Limes Brown	stone 14 28 Stone 28 28 42 Stone 42 160 Stone 5 28 28 42 Stone 6 160 270 Sandstone 2 Ventanta 28 28 28 270 Sandstone 2 Ventanta 28 28 28 270 Sandstone 3 Ventanta 28 28 28 28 28 28 28 28 28 28 28 28 28		
7. Dia. (in.)	New BI	Casin Material, W unfacturer & K ST 1	5. 6. 7. g, Linereight, Special Method	Cable-tool Bi Temp. Outer Removed? If no, explain Other T, Screen pecification d of Assembly STM A-5	casing 1 Yes a why not	oin. dia No	To (ft.)	10. Static	Limes White Limes Brown Hard Firm	stone 14 28 stone 28 42 stone 42 160 Sandstone 28 42 160 Sandstone 28 42 160 270 Gray Sandstone 19 19 19 19 19 19 19 19 19 19 19 19 19		
7. Dia. (in.)	New BI	Casin Material, W unfacturer & K ST 1	5. 6. 7. g, Linereight, Special Method	Cable-tool Bi Temp. Outer Removed? If no, explain Other T, Screen pecification d of Assembly STM A-5	casing 1 Yes a why not	Oin. dia No From (ft.) surface	To (ft.)	algmes	Limes White Limes Brown Hard Firm Water Lev	stone 14 28 stone 28 42 stone 42 160 Sandstone 42 160 Sandstone 42 160 Cray Sandstone 270 325 Light Green Sandstone 325 360 rel 12. Well Is: Above Grade		
7. Dia. (in.)	Man New BI 19.45	Casin Material, W sufacturer & K ST 1 lbs Sa	5. 6. 7. g, Linereight, Sp. Method	Cable-tool Bi Temp. Outer Removed? If no, explain Other T, Screen pecification d of Assembly STM A-5	Casing	oin. dia No	To (ft.)	algmes	Limes Limes Brown Hard Firm Water Lev	stone 14 28 Sandstone 28 42 Stone 42 160 Sandstone 160 270 Gray Sandstone 270 325 Light Green Sandstone 325 360 Vel 12. Well Is: Above Grade Below Grade Below Grade		
7. Dia. (in.)	Man New BI 19 45	Casin Material, Waufacturer & K ST 1 The Sa	5. 6. 7. g, Linereight, Sp. Method	Cable-tool Bi Temp. Outer Removed? If no, explain Other T, Screen pecification d of Assembly STM A-5 1 IISA	Casing	From (ft.)	To js (ft.) 180 an older	21 11. Pump	Limes White Limes Brown Hard Firm Water Lev ft. 80 ft.	stone 14 28 Sandstone 28 42 Stone 42 160 Sandstone 160 270 Gray Sandstone 270 325 Light Green Sandstone 325 360 Vel 325 Above ground surface 320 in. Below Grade Below Grade Developed? Yes No		
7. Dia. (in.)	Man New BI 19 45	Casin Material, W sufacturer & K ST 1 lbs Sa	5. 6. 7. g, Linereight, Sp. Method	Cable-tool Bi Temp. Outer Removed? If no, explain Other T, Screen pecification d of Assembly STM A-5 1 IISA	Casing	oin. dia No	To is (ft.)	21 11. Pump Pump	Limes White Limes Brown Hard Firm Water Level ft. Test ing Level	stone 14 28 Sandstone 28 42 Stone 42 160 Sandstone 160 270 Gray Sandstone 270 325 Light Green Sandstone 325 360 Vel 12. Well Is: Above Grade Below ground surface 20 in. Below Grade Developed? Yes No Developed? Yes No Carred? Yes No Carred? Yes No No Carred?		
7. Dia. (in.) Dia. (in.)	New BI 19.45	Casin Material, W. ufacturer & K. ST. 11 1 hs. Sa	5. 6. 7. g, Linereight, Speak Method	Cable-tool Bi Temp. Outer Removed? If no, explain Other T, Screen pecification d of Assembly STM A-5 1 IISA	Casing	From (ft.)	To (ft.)	21 11. Pump Pump Pump	Limes White Limes Brown Hard Firm Water Level ft. 80 ft. Test ing Level ing at	stone 14 28 Sandstone 28 42 Stone 42 160 Sandstone 160 270 Gray Sandstone 270 325 Light Green Sandstone 325 360 Vel 12. Well Is: above ground surface below ground surface below ground surface 10 Developed? Yes No Developed? Yes No Capped? Yes No No Capped? Yes No		
7. Dia. (in.) Dia. (in.) 8. Grout of	New BI 19.45	Casin Material, W. Wufacturer & K. ST. 11 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	5. 6. 7. g, Linereight, Sp & Method CC A	Cable-tool Bi Temp. Outer Removed? If no, explain Other , Screen pecification d of Assembly STM A-5 1 IISA	Casing	From (ft.)	To js (ft.) 180 an older	11. Pump Pump Pump Pump 13. Did yo on thi	Limes Brown Hard Firm Water Level sing Level sing at	Sandstone 28 42 Stone 42 160 Sandstone 42 160 Sandstone 270 325 Light Green Sandstone 325 360 Vel 12. Well Is: Above Grade Below ground surface below ground surface below ground surface Developed? Yes No Developed? Yes No Capped? Yes No No Capped? Yes No No Che owner of the need to permanently abandon and fill all unused wells?		
7. Dia. (in.) Dia. (in.) 8. Grout of	New BI 19.45	Casin Material, W. ufacturer & K. ST. 13 108 Sa	5. 6. 7. g, Linereight, Sp & Method CC A	Cable-tool Bi Temp. Outer Removed? If no, explain Other , Screen pecification d of Assembly STM A-5 1 IISA	Casing 1 Yes Casin	From (ft.) From	To (ft.) 180 To # Sacks Cement	11. Pump Pump Pump Pump 13. Did yo on thi	Limes Brown Hard Firm Water Level ft. 80 ft. Test ing Level ing at	Stone 14 28 Stone 28 42 Stone 42 160 Sandstone 160 270 Gray Sandstone 270 325 Light Green Sandstone 325 360 Vel 12. Well Is: above ground surface below ground surface below ground surface 12. Well Is: above ground surface 20 in. Below Grade Below Grade Developed? Yes No Developed? Yes No Capped? Yes No No Capped? Yes No No Capped? Yes No No Capped? Yes No No Capped? No The owner of the need to permanently abandon and fill all unused wells?		
7. Dia. (in.) 6 Dia. (in.) 8. Grout of Method	New BI 19.45	Casin Material, W ufacturer & K ST 1 lbs Ss e, material ling Material Sealing Ma	5. 6. 7. g, Linereight, Sp & Method CC A	Cable-tool Bi Temp. Outer Removed? If no, explain Other , Screen pecification d of Assembly STM A-5 1 IISA	Casing 1 Yes [a why not 2 3 GR B	From (ft.) From	To (ft.) 180 To # Sacks	11. Pump Pump Pump 13. Did yo on thi	Brown Hard Firm Water Level ing at ou notify to s property es ture of Poi	Sandstone 28 42 Stone 42 160 Sandstone 160 270 Gray Sandstone 270 325 Light Green Sandstone 325 360 Vel 325 Light Green Sandstone 325 360 Vel 325 Above Grade Below Grade Below Grade Below Grade Developed? Yes No Disinfected? Yes No Capped? Yes No Capped? Yes No Capped? Yes No Capped? Yes No The owner of the need to permanently abandon and fill all unused wells on the owner of the need to permanently abandon and fill all unused wells on the owner of the need to permanently abandon and fill all unused wells on the owner of the need to permanently abandon and fill all unused wells on the owner of the need to permanently abandon and fill all unused wells on the owner of the need to permanently abandon and fill all unused wells on the owner of the need to permanently abandon and fill all unused wells on the owner of the need to permanently abandon and fill all unused wells on the owner of the need to permanently abandon and fill all unused wells on the owner of the need to permanently abandon and fill all unused wells on the owner of the need to permanently abandon and fill all unused wells on the owner of the need to permanently abandon and fill all unused wells on the owner of the need to permanently abandon and fill all unused wells on the owner of the need to permanently abandon and fill all unused wells on the owner of the need to permanently abandon and fill all unused wells on the owner of the need to permanently abandon and fill all unused wells on the owner of the need to permanently abandon and fill all unused wells on the owner of the need to permanently abandon and fill all unused wells on the owner of the need to permanently abandon and fill all unused wells on the owner of the need to permanently abandon and fill all unused wells on the owner of the need to permanently abandon and fill all unused wells on the owner of the need to permanently abandon and fill all unused wells on the owner of the need to permanently abandon and fill all unused wells on the owner of the need to permanently abandon		
7. Dia. (in.) 6 Dia. (in.) 8. Grout of Method	New BI 19.45 screen type or Other Seal	Casin Material, W ufacturer & K ST 1 lbs Ss e, material ling Material Sealing Ma	5. 6. 7. g, Linereight, Sp & Method CC A	Cable-tool Bi Temp. Outer Removed? If no, explain Other , Screen pecification d of Assembly STM A-5 1 IISA	Casing 1 Yes a why not Grant Transfer of the control of the contr	From (ft.) From (ft.)	To (ft.) 180 To # Sacks Cement	11. Pump Pump Pump 13. Did yo on thi	Brown Hard Firm Water Level ing at ou notify to s property es ture of Poi	Sandstone		
7. Dia. (in.) 6 Dia. (in.) 8. Grout of Method	New BI 19.45 screen type or Other Seal Kind of Sea	Casin Material, Woufacturer & K ST 11 10 Se	5. 6. 7. g, Linereight, Sp. Method	Cable-tool Bi Temp. Outer Removed? If no, explain Other , Screen pecification d of Assembly STM A-5 1 IISA	Casing 1 Yes Casing 1 Yes Casing 1 Yes Casing 1 Yes Casing 1 From (ft.) Surface	From (ft.) From (ft.) To (ft.) 180	To (ft.) 180 To # Sacks Cement 82	11. Pump Pump Pump 13. Did yo on thi Y 14. Signa Signature	Limes Brown Hard Firm Water Level ing Level ing Level ou notify t s property es ture of Poi of Drill R	Stone 14 28 Stone 28 42 Stone 42 160 Sandstone 160 270 Gray Sandstone 270 325 Light Green Sandstone 325 360 Vel 325 Light Green Sandstone 325 360 Vel 300 ft. below surface below ground surface below ground surface Developed? Yes No Disinfected? Yes No Capped? Yes No Capped? Yes No Mo Capped? Yes No Mo Capped? Yes No Mo Capped? Yes No Disinfected? Yes No Capped? Yes No Capped? Yes No Capped? Yes No Disinfected? Yes No Capped? Yes No Disinfected? Yes No Yes No Capped? Yes No Disinfected? Yes No Yes No Yes No Yes No Yes No Yes No Disinfected? Yes No Y		

WELL OWNED